

Junction box

WKE 203 SL



WKE 203 SL

Junction box

Productnumber: 86228301

Dimensions: 115 x 115 x 93 mm

Junction box, protection class IP66, $U_i=450$ V AC, certified by VDE (DIN EN 60670-1/-22 (VDE 0606-1/-22)), internal thread, M25, (3 side), external fixing lugs, with E30 electrical functional integrity according to DIN 4102 Part 12, with screwless Wago TopJobS terminal blocks, enclosure made from halogen-free special thermosetting plastic

orange, junction box 3-pole, clamping capacity per pole $4 \times 0.5 - 4 \text{ mm}^2$

Accessories supplied:

3 cable glands M25, seal range 6 - 15 mm, Wall plug set $\varnothing 6$ mm



Technical Data

electrical characteristics

Rated insulation voltage AC:	450 V
Rated insulation voltage DC:	450 V
Min. conductor cross section:	0,5 mm²
max. wire cross section (wire branching):	4 mm²
Min. conductor cross section:	0,5 mm²
Max. conductor cross section:	4 mm²
Protection class:	II
Type of protection:	IP66
Circuit integrity class:	E30
Number of poles (T-piece):	3
Number of poles (feed-through):	3
UL Type Rating:	not specified

Colours

Base unit colour:	orange
Cover colour:	orange

Additional features

Range of application:	Connectors and T-pieces
-----------------------	-------------------------

Dimensions

Width:	115 mm
Length:	115 mm
Height:	93 mm
Weight:	1.45 kg

Material characteristics

UV-resistant:	yes
Halogen free:	yes
Flammability class according with UL94:	V0

Material characteristics

Glow-wire flammability according to EN 60695-2-11:	960 °C
--	--------

mechanical properties

Impact strength:	IK08
Sealable:	no
Cover screw torque:	2.5 Nm
Type of fastening:	Wall/ceiling mounting
Fastening:	external fixing lugs

Ambient conditions

max. relative humidity 25°C:	95 %
max. relative humidity 40°C:	50 %
Min. ambient temperature:	-25 °C
Max. ambient temperature:	40 °C
24h ambient temperature:	35 °C
Installation location:	protected outdoor areas

Sales Information

EAN:	4013902668656
Packing Unit Code:	CT
ETIM Class:	EC002600
Custom tariff number:	85369095

Material

Base unit material:	Duroplast
Cover material:	Duroplast
Sealing material:	Polyurethane
Cover screw material:	Stainless steel V2A

Certificates

Test mark:	VDE (DIN EN 60670-1/-22 (VDE 0606-1/-22))
------------	---

Accessories

[86040001 - WKE 200 ABL - External attachment set](#)

Cable gland

