


Junction box

WKE 2 - 5 x 1,5²



WKE 2 - 5 x 1,5²

Junction box

Productnumber: 86650201

Dimensions: 100 x 100 x 70 mm

Junction box, protection class IP66, $U_i=450$ V AC, certified by VDE (DIN EN 60670-1/-22 (VDE 0606-1/-22)), UL-EU (EN 62208), knockouts, M16/M25, (1 rear, 7 side), external fixing lugs, with E30 - E 90 electrical functional integrity according to DIN 4102 Part 12. Halogen-free enclosure made of special thermoplastic, terminals made of high-temperature-resistant special ceramic, universally positionable terminal holder

orange, junction box, 5-pole, 0.5 - 4 mm², junction box 5-pole 0.5 - 1.5 mm², number of clampable wires per pole:
8 x 0.5² / 4 x 0.75² / 6 x 1² / 6 x 1.5² / 2 x 4²

Accessories supplied:

Cover retainer, screw anchors, 4 double membrane seals IP66 M25 sealing range 9 - 17 mm



Technical Data

electrical characteristics

Rated insulation voltage AC:	450 V
Rated insulation voltage DC:	450 V
Min. conductor cross section:	0,5 mm²
max. wire cross section (wire branching):	1,5 mm²
Min. conductor cross section:	0,5 mm²
Max. conductor cross section:	4 mm²
Protection class:	II
Type of protection:	IP66
secured junction:	no
Circuit integrity class:	E30/E60/E90
Number of poles (T-piece):	5
Number of poles (feed-through):	5
UL Type Rating:	other
Number of fuses in T-piece:	0

Colours

Base unit colour:	orange
Cover colour:	orange

Additional features

Range of application:	Connectors and T-pieces
-----------------------	-------------------------

Dimensions

Width:	100 mm
Length:	100 mm
Height:	70 mm
Inner length:	87 mm
Inner width:	87 mm
Inner height:	52 mm
Weight:	0.43 kg

Material characteristics

UV-resistant:	yes
Halogen free:	yes
Flammability class according with UL94:	V0
Glow-wire flammability according to EN 60695-2-11:	960 °C

mechanical properties

Type of fastening:	Wall/ceiling mounting
Impact strength:	IK08
Sealable:	yes
Fastening:	external fixing lugs

Ambient conditions

max. relative humidity 25°C:	95 %
max. relative humidity 40°C:	50 %
Min. ambient temperature:	-35 °C
Max. ambient temperature:	80 °C
24h ambient temperature:	60 °C
Installation location:	protected outdoor areas

Sales Information

EAN:	4013902630974
Packing Unit Code:	C62
ETIM Class:	EC002600
Custom tariff number:	85369095

Material

Base unit material:	Polycarbonate
Cover material:	Polycarbonate
Sealing material:	Polyurethane
Cover screw material:	Stainless steel V2A

Certificates

Test mark:	VDE (DIN EN 60670-1/-22 (VDE 0606-1/-22))
------------	---

Test mark:	UL-EU (EN 62208)
------------	------------------

Accessories

[26061601 - DMS M16/or - Double-membrane seals](#)

[26062501 - DMS M25/or - Double-membrane seals](#)

[22761601 - KVR M16-MGM/or - Cable gland](#)

[22762501 - KVR M25-MGM/or - Cable gland](#)

[26062001 - DMS M20/or - Double-membrane seals](#)

[86310001 - WKE BK 1 - Mounting plate](#)

Cable gland

